

- 1280 X 720P LIVE VIEWING RESOLUTION AND RECORDING
- REAL TIME H.264 COMPRESSION VIDEO DATA
- QUICK CONNECT TECHNOLOGY TO CONNECT FROM MOBILE AND AVOID MORE PORT FORWARDING AND ROUTER CONFIGURATIONS
- SENSOR AND ALARM: 8CH SENSOR INPUT & 1 ALARM OUT
- SUPPORTS IR REMOTE CONTROL AND PTZ CONTROL
- BACKUP HDD DATA VIA SATA PORT
- HDMI AND VGA OUTPUTS
- SUPPORTS MOBILE SURVEILLANCE



GENERAL DESCRIPTION

Our new **SVR9000AHD** series of digital video recorders has been designed to deliver stunning high definition **720p** recording in an analog format that doubles the current standard recording resolution of **960H**. The **SVR9000AHD** series records at the best quality of **720p** on every channel for the 4, 8, and 16 channel models. This generation of DVRs comes with an E-SATA interface for backup and high-speed connection with an external HDD for larger storage. The HDMI and VGA outputs allow you to connect to HD monitors or TVs improving the playback experience.

Every DVR includes Quick Connect Technology eliminating the need to manually port forward or utilize DDNS servers. Quick connect technology automatically opens these ports to communicate with your router and includes an ID or QR code specific to that DVR. Each QR code can be scanned using our Bolide DVR application available on iOS or Android devices and will enable the user to automatically sync to their DVR and immediately gain access to their system.

The **SVR9000AHD** series utilizes a free licensed CMS that features a digital zoom option over live view and playback. The CMS can fully manage up to 128 DVR's and allow for live viewing of up to 64 video streams.



SPECIFICATIONS		SVR9008AHD
VIDEO COMPRESSION		H.264
VIDEO SYSTEM		PAL/NTSC
OPERATION SYSTEM		Linux(embedded)
VIDEO	INPUT	8CH input BNC
	OUTPUT	1CH output BNC
AUDIO	INPUT	4CH input RCA
	OUTPUT	1CH output RCA
DISPLAY	RESOLUTION	NTSC:1280*720P or 960*480@30fps(each Ch) PAL:1280*720P or 960*576@25fps(each Ch)
	FEATURE	single/ Quad/Nine/S.E.Q.
RECORD	RESOLUTION	NTSC: 1280*720P or 960*480 PAL: 1280*720P or 960*576
	FRAME RATE	NTSC: 1280*720P @15fps(each Ch) / 960*576 @30fps(each Ch) PAL: 1280*720P @12fps(each Ch) / 960*576 @25fps(each Ch)
RECORDING MODE		Continuous/Manual/Motion detected
PLAYBACK CHANNEL		Local DVR: 1~8ch PC/MAC: 1~4ch Smart Phones: 1ch (using app) Tablets: 1~4ch
PLAYBACK SPEED		PAL:1280*720P @12fps(each Ch) / 960*576 @25fps(each Ch) NTSC: 1280*720P @15fps(each Ch) / 960*576 @30fps(each Ch)
SENSOR & ALARM I/O		8ch sensor input 1 channel alarm out
NETWORK TYPE		Lan, DHCP and DDNS
HDD INTERFACE		1 SATA HDD, up to 4TB
MULTIPLEX OPERATION		live display, record, playback, backup and network
USB		2xUSB(for mouse and backup/upgrade)
PTZ CONTROL		Yes
MOBILE SURVEILLANCE		Support Mobile Phones based on iPhone and Android operation system
VGA		800*600,1024*768, 1280*1024,1440*900, 1920*1080
HDMI		1080p
IR EXTENDER PORT		Yes
E-SATA		For Backup
QUICK CONNECT TECHNOLOGY		Yes
POWER SUPPLY		DC 12V 2A
DIMENSION (WxDxH)		315mmx220mmx50mm