

- This powerful 16Port Managed PoE Ethernet Switch, provides 16*100Mbps downlink PoE Ethernet ports, supports IEEE802.3 af/at and 2*1000Mbps uplink optical ports and 2*1000Mbps uplink Ethernet ports
- Provide web-based layer 2 network management and PoE management with simple operation process:
- Support high-speed data forwarding, perfectly designed for the large flow of video data forwarding required in security surveillance
- Support one-key recovery of IP address & user password;
- Excellent circuit isolation protection, lightning protection up to 2KV
- Quick installation, easy operation and convenient for wall / desk/ rack installation


POWER

POWER SUPPLY	Mains on load
VOLTAGE RANGE	AC 100-240V
CONSUMPTION	320W

NETWORK CONNECTOR

ETHERNET PORT	1-16, ports: 10/100Mbps Ethernet Port Adaptive control UPLINK Ethernet port: 10/100/1000Mbps Ethernet Port SFP: SFP optical fiber module, 1000Mbps
TRANSMISSION DISTANCE	1-16ports: Recommended 120m Max. 150m; Uplink1000Mbps ethernet port: Ma.x150m SFP: depends on the optical module performance

PoE PROTOCOL	IEEE802. 3af. IEEE802. 3at
---------------------	----------------------------

PoE POWER SUPPLY	End-span
-------------------------	----------

PoE POWER CONSUMPTION	Each Port ≤30W Total ≤250W
------------------------------	-------------------------------

NETWORK SWITCH

NETWORK STANDARD	IEEE802.10BASE-T, IEEE802. 3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802. 3Z 1000BASE-SX/LX
-------------------------	--

SWITCH CAPACITY	16G
------------------------	-----

MANAGEMENT

MANAGEMENT	Management L2
-------------------	---------------

PROTECTION

ESD	Level 3, Per IEC61000-4-2
------------	---------------------------

COMMUNICATION PORT LIGHTNING PROTECTION	Level 3, Per IEC61000-4-5
--	---------------------------

ENVIRONMENTAL

WORKING TEMPERATURE	0°C - 55°C / 32F - 131F
----------------------------	-------------------------

STORAGE TEMPERATURE	-40°C - 85°C / -40F - 185F
----------------------------	----------------------------

HUMIDITY (Non-condensing)	0-95%
----------------------------------	-------

MECHANICAL

DIMENSION (LxWxH)	442mmx315mmx44mm
--------------------------	------------------

MATERIAL	Sheet metal
-----------------	-------------

COLOR	Black
--------------	-------